

QIS

Quick Installation System



The main trunking unit (QIS) - quick installation system houses cables which supply power to the luminaire as well as provide cabling for track lights, emergency lighting, cameras, sensors and DALI. QIS provides the ability to move lighting within the trunking unit as well as change lighting configuration with minimal cost and work time.

Our QIS system is ideal for locations where the lighting configuration is not fixed. Including warehouses with mobile racking units and retail stores with changing layouts.

This system allows for rapid lighting configuration reducing the costs and time of installation. Every unit can be fitted with a maximum of 11 wires using WAGO connectors - SWEWxxx / SWETxxx

TECHNICAL DATA



RoHS

Mechanical Data

Length	1000 mm / 2000 mm / 3000 mm 4000 mm / 5000 mm / 6000 mm
Height	37 mm
Weight	80 mm
Casing	aluminium
Casing Colour	silver / black
IP	IP20 / IP65*
Operating Temperature	+5°.....+35C°
Installation	on the slings, surface mounted
Installation Cable	max 7x2,5mm ²
Warranty	5 Years

* - optional

Electrical Data

Voltage	230V / 110V*
----------------	--------------

* - optional

Application

warehouses, industrial halls, production plants, commercial buildings, sports facilities, public facilities

Parameters

Index	IP	Installation Cable [mm ²]
QIS(X).3x1,5.22/EU	IP20	3x1,5
QIS(X).5x1,5.22/EU	IP20	5x1,5
QIS(X).7x1,5.22/EU	IP20	7x1,5
QIS(X).9x1,5.22/EU	IP20	9x1,5
QIS(X).11x1,5.22/EU	IP20	11x1,5
QIS(X).3x2,5.22/EU	IP20	3x2,5
QIS(X).5x2,5.22/EU	IP20	5x2,5
QIS(X).7x2,5.22/EU	IP20	7x2,5
QIS(X).5x1,5+4x2,5.22/EU	IP20	5x1,5 + 5x2,5
QIS(X).7x1,5+4x2,5.22/EU	IP20	7x1,5 + 4x2,5
QIS(X).3x1,5.22/EU	IP65	3x1,5
QIS(X).5x1,5.65/EU	IP65	5x1,5
QIS(X).7x1,5.65/EU	IP65	7x1,5
QIS(X).9x1,5.65/EU	IP65	9x1,5
QIS(X).11x1,5.65/EU	IP65	11x1,5
QIS(X).3x2,5.65/EU	IP65	3x2,5
QIS(X).5x2,5.65/EU	IP65	5x2,5
QIS(X).7x2,5.65/EU	IP65	7x2,5
QIS(X).5x1,5+4x2,5.65/EU	IP65	5x1,5 + 5x2,5
QIS(X).7x1,5+4x2,5.65/EU	IP65	7x1,5 + 4x2,5

* (X) = 1 / 2 / 3 / 4 / 5 / 6



Dimensions

Index	L [mm]	W [mm]	H [mm]
QIS1	1000	80	37
QIS2	2000	80	37
QIS3	3000	80	37
QIS4	4000	80	37
QIS5	5000	80	37
QIS6	6000	80	37

